

ZPD204A

New



4 Channel H.264

Full - D1 Networking DVR



| Model | | ZPD204A |
|-----------------------|----------------------|--|
| Special function | P2P function (IE) | Using Device ID and password to login www.vssweb.net, realize remote monitoring, playback and control like IE Web login. No need any network, IP setting, easy for end user to use network function. |
| | Web 2.0 function | Support multi brower, like: chrome,firefox,safari etc. realize remote display, playback. |
| System | Operation System | Embedded LINUX |
| | Pentaplex function | Live monitoring, recording, playback, backup & remote access |
| | Control Mode | USB mouse, Network |
| Video | Input | 4 ch. BNC |
| | Standard | PAL (625line, 50f/s) NTSC (525line, 60f/s) |
| | Output | 1 CVBS, BNC (1.0Vp-p,75 ohms) |
| | | 1 HDMI, 1.3a,support 1920x1080 Resolution |
| | | 1 VGA,1920x1080,1280x1024,1280x720,1024x768 Resolution |
| Audio | Input | 1 ch. RCA(Line in,2Vpp,1Kohms) |
| | Output | 1 RCA (Line out,2Vpp,300ohms) |
| Display | Tour Display | Support |
| | Privacy Masking | Four zones for privacy masking for each channel |
| Recording | Video Compression | H.264 |
| | Audio Compression | G.711A |
| | Image Encoding | Adjustable encoding quality, variable code stream/fixed code stream |
| | Dual Stream | Support |
| | Recording Resolution | 960H |
| | Recording Mode | Manual, Schedule, motion detection, stop |
| | Time bar | Support |
| Video Detection&Alarm | Trigger Events | Recording, Tour,Email |
| | Motion Detection | 396 (22x18) detection zone, variable sensitivity levels |
| | Capture | JPEG capture |
| Playback&Backup | Playback Channel | 1/2/4 ch. |
| | Backup Mode | USB,HDD,Network Backup |
| Network | Ethernet | 1 RJ-45 port (10M/100M) |
| | Network protocol | TCP/IP, UDP, HTTP, RTP/RTSP |
| | Network Functions | DHCP, PPPOE, DDNS, SMTP, SNTP, FTP, UPnP |
| | Remote Operation | Monitoring, PTZ control, playback, system setting, file download, log information |
| | Smart Phone | iPhone, iPad, Android, BlackBerry, Windows Mobile |
| Hard Disk | Hard Disk | 1 SATA ports |
| | HDD Management | Hard disk hibernation technology, HDD faulty alarm&raid |
| Auxiliary Interface | USB Interface | 2 USB 2.0 ports |
| Environment | Power Supply | DC12V/2A |
| | Power Consumption | 10W (without HDD) |
| | Working Environment | 0°C—+45°C / 10%—90%RH |
| | Dimension(W*D*H) | 1U, 215x215x46mm(WxDxH) |
| | Weight | 0.8Kg (without HDD) |
| | Installation | Desk type |