



ZPN501A

MODEL		SPECIFICATIONS
<i>Special function</i>	<i>P2P function</i>	Using Device ID and password to login www.vssweb.net , realize remote monitoring, playback and control like IE Web login. No need any network, IP setting, easy for end user to use network function.
System	Operation System	Embedded LINUX
	Pentaplex function	Live monitoring, recording, playback, backup & remote access
	Control Mode	USB mouse, Network
Video	IP Camera Input	4ch.(32Mbps)
	Decoding Capability	4ch.D1@30fps 4ch.720P@30fps 2ch.1080P@30fps
	Support Protocol	ONVIF
	Standard	PAL (625line, 50f/s) NTSC (525line, 60f/s)
	Output	1 CVBS, BNC (1.0Vp-p,75 ohms)
		1 HDMI, 1.3a,support 1920×1080 Resolution 1 VGA,1920×1080,1280×1024,1024×768 Resolution
Audio	Output	1 RCA(2.0Vp-p,300 ohms)
	Two-way Talk	1st channel reuse
Display	Frame	1-30fps
	Tour Display	Support
	Privacy Masking	Four zones for privacy masking for each channel
Recording	Video Compression	MPEG-4/H.264(High Profile@Level4.2)
	Audio Compression	G.711A
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
	Dual Stream	Support
	Recording Mode	Manual, scheduled, motion detection, stop
	Time bar	Support
Video Detection&Alarm	Trigger Events	Recording, Tour, Email
	Motion Detection	396 (22×18) detection zone, variable sensitivity levels
	Capture	JPEG capture
Playback&Backup	Max Playback	1/2/4 ch.
	Backup Mode	USB,HDD,Network Backup
Network	Ethernet	1 RJ-45 port (10M/100M)
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
	Network Functions	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
	Remote Operation	Monitoring,playback,system setting,file download,log information
	Smart Phone	iPhone,iPad,Android
Hard Disk	Hard Disk	1 SATA port,each SATA supports 4TB
	HDD Management	Hard disk hibernation technology, HDD faulty alarm
Auxiliary Interface	USB Interface	2 USB 2.0 ports
Environment	Power Supply	DC12V/2A
	Power Consumption	5W (without HDD)
	Working Environment	0°C~+45°C / 10%~90%RH
	Dimension(W*D*H)	215x215x50mm(W×D×H)
	Weight	0.8Kg (without HDD)
	Installation	Desk type