

ZAS723 Speed Dome Camera

iNNEKT






Innovative Technology

23x IR High Speed Dome Camera

- PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor;
- IR distance 130~150M; Multiple languages for OSD menu;
- Support ambient light detection, IR illumination on 1-15 grades selectable;
- 64 bit CPU, slow speed rate 0.05°/s, accuracy 0.01°, smooth and even motion;
- Time scheduling function;
- Remote Firmware upgrade via the RS485 bus;
- Dome ID, baud rate, communication protocol can be set via the controller;
- Supported Protocols: Pelco-D/P; Others on special request;
- 7" total metal body construction, waterproof IP66;
- Optional IP module (built in provision);
- Optional, 4 alarm inputs and 2 alarm outputs.



Dimensions



Specification

Model No.	ZAS723
DSP	Sony Effio-e DSP(673)
Sensor	1/3" SONY Exview HAD CCD II
Signal Standards	PAL / NTSC
Resolution	700Tvl
Lens	30X optical Zoom, F=3.9mm ~ 117mm
IRCut	With IRCut
Pixels	PAL: 967(H)x494(V) / NTSC: 960(H)x582(V)
Min.Illumination	0.01Lux
Day/Night	Color/W&B/Auto
Synchronization	Internal Synchronization
SNR	≥ 48dB
White Balance	Auto/Indoor/Outdoor/Manual
Focus Mode	AUTO/Manual
BLC	Support
Horizontal Rotation Speed	0.02 ~ 300°/s
Tilt Rotation Speed	0.02 ~ 160°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	90°
Auto Flip	Horizontal 180°, Vertical 93°
Auto Control IR LED	PWH
360° Scan	1-64 levels setting available
A-B Scan	User programmable
A-B Scan Speed	1-64 levels setting available
PWR on Action	Memory / Pattern 1/ Tour 1 / 360 scan / A-B scan / Preset 1-8
Dwell Preset	5-60s interval available
Preset Points	220
Go to Preset Speed	1-64 levels available
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Pattern Scan	4 pcs
Pattern Scan Record	Max.15 minuter, max.512 commands
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
Privacy Mask	8-24pcs (according to zoom module type)
OSD Menu	Multiple Languages
3D Location	Support
Time Scheduling Function	8 tasks
Operating Temperature	Indoor: 0°~ +40°, Outdoor: -40°~ +60°
Operating Humidity	≤ 95% Non Condensing
Heater & Blower	Auto temperature control
Power	AC/DC15-28V ≤ 3A
Power Consumption	≤ 25W
Lightning Protection	Transient voltage 6000V
IR Leds	10pcs Ø20 IR LEDs
IR distance	130 ~ 150M